

TUNZE®

Aquatic Eco Engineering

SMART & TUNZE® CONTROLLER HUB



5 years warranty

Made in Germany

Uncomplicated
"over the air" updates

5 year update guarantee

Failsafe: Internet only for
configuration & notification
necessary. Not for operation.

Including temperature probe

Including wall mount

Integrated real time clock:
→ No program shift
in case of power failure

Precise pH or redox measurement

SmartController 7000.001

With temperature probe, 4 connection cables,
universal connection cable, mounting set.
Dimensions without mount (L x W x H):
133 x 33 x 116 mm (5.2" x 1.2" x 4.5")

Controls up to:

- 4xTUNZE® switched socket / valve
- 4xTUNZE® LED 8850 / Kessil® 0-10V
- 4xTUNZE® Turbelle® electronic / 0-10V pump
- 4xTUNZE® Aquawind



One platform – many end devices

All compatible devices can be clearly managed
in one place on the TUNZE® HUB.



Funding from hardware, no hidden
operating costs.

Browser-based web interface:
operating system independent,
no drivers, no programs.

No hidden data collection.

Measured values are permanently
secured online and can be viewed online.

Redundant servers at different locations
in Europe.

Control: Fully configurable
reaction system.

Complete communication encrypted.
Server to end device as device-individual
AES256 encryption.

Fully configurable notification system.

Start Foodtimer

Info Screens



Main Menu

